

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

## 1. Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier: PRIMER CAPS MEDIUM 6.17MM SINOXID  
7213
- 1.2 Identified uses: The article is intended for professional use.
- 1.3 Details of the supplier of the safety data sheet:  
 Manufacturer: RUAG Ammotec GmbH  
 Street: Kronacher Str. 63  
 Postal code / City: 90765 Fürth  
 Country: Germany  
 Telephone: +49 911 7930 0  
 Telefax: +49 911 7930 680  
 E-mail (competent person): sicherheitsdatenblaetter.ammotec@ruag.com  
 Information contact: +49 911 7930 289 (technical support)
- 1.4 Emergency telephone number: +49 911 7930 0

## 2. Hazards identification

- 2.1 Classification of the substance or mixture:  
 2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]:  
 Hazard classes and hazard categories: Expl. 1.4, H204
- 2.2 Label elements:  
 2.2.1 Labelling according Regulation (EC) No 1272/2008 [CLP]:

Hazard pictograms:



Signal word: **Warning**

Hazard statements: H204

Precautionary statements: P210

P234

P250

P280

P370+380+375

P401

Fire or projection hazard.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep only in original container.

Do not subject to grinding/shock/.../friction.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Store in accordance with: national regulations

- 2.3 Other hazards:  
 This article contains hazardous substances or mixtures not intended to be released under normal or reasonably foreseeable conditions of use.

- 2.3.1 Adverse physicochemical effects:  
 This article can be ignited by heat, sparks, flames or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

- 2.3.2 Adverse human health effects and symptoms:  
 The dismantling of the article is prohibited.  
 Please observe in any case the safety information.

Remark						Material No. 2101491			
Title <b>PRIMER CAPS MEDIUM 6.17 MM SINOXID</b>									
<b>RUAG</b>	Protection notices DIN ISO 16016		Name	Date	Doc-Typ <b>ZSD</b>	Document <b>362361</b>	Part <b>EN0</b>	Version <b>00</b>	Page <b>1/7</b>
		Created	RTWIRO	20.02.2019					
		Released	RTWIRO	20.02.2019					

2012-08-16

Dok-Status: FR

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

## 3. Composition/information on ingredients

### 3.1 Mixtures:

Substance name	EG-No.	REACH-Reg.-No.	Index-No.	CAS-No.	Concentration (%)	Classification according to Regulation (EC) No 1272/2008	
						Hazard classes/ Hazard categories	Hazard statements
Lead styphnate	239-290-0	01-2119543737-30	609-019-00-4	15245-44-0	1 – 3	Unst. Expl. Repr. 1A Acute Tox. 4 STOT RE 2 Aquatic acute 1 Aquatic chronic 1	200 360Df 302, 332 373 400 410
Barium nitrate	233-020-5	01-2119986880-22	056-002-00-7	10022-31-8	1 – 3	Ox. Sol. 2 Acute Tox. 4	272 302, 332
Antimony(III)-sulphide	215-713-4	01-2119951854-28	051-003-00-9	1345-04-6	0.1 – 1	Carc. 2	351

### 3.2 Remark:

Further ingredients are below the cut-off values according to regulation (EC) 1272/2008 or possess only physicochemical properties.

Full text of H- and EUH-phrases: see section 16.

## 4. First aid measures

### 4.1 General information:

First aid measures only required by release of ingredients or generation of decomposition products.  
Medical treatment necessary.

- 4.2 Following inhalation: In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. Apply cortisone spray at early stage.
- 4.3 Following skin contact: After contact with skin, wash immediately with soap and plenty of water.
- 4.4 Following eye contact: In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
- 4.5 Following ingestion: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.
- 4.6 Self-protection of the first aider: First aider: Pay attention to self-protection!

### 4.7 Notes for the doctor:

If decomposition products are inhaled the following symptoms can occur:

Unconsciousness, Impaired consciousness, Cyanosis (blue coloured blood), Vomiting, Cardiac arrhythmias, Headache, Spasms, Circulatory collapse, Dizziness, Impairment of vision, Nausea

Treatment:

Supervise the blood circulation. Regulation of the blood circulation, possible shock treatment.  
Where appropriate artificial ventilation.

In the case of bluish discoloration (lips, earlobes, finger nails) give oxygen as soon as possible.

In the case of lung irritation: Primary treatment by using Corticoid spray, e.g. Auxilison spray, Pulmicort-dosage-spray (Auxilison and Pulmicort are registered trademarks).

## 5. Fire-fighting measures

- 5.1 Suitable extinguishing media: Water and extinguishing powder from safe distance at fire in the surroundings.
- 5.2 Extinguishing media which must not be used for safety reasons: not applicable.

Title <b>PRIMER CAPS MEDIUM 6.17 MM SINOXID</b>								
<b>RUAG</b>	Protection notices DIN ISO 16016			Doc-Typ	Document	Part	Version	Page
				<b>ZSD</b>	<b>362361</b>	<b>EN0</b>	<b>00</b>	<b>2/7</b>

Dok-Status: FR

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

- 5.3 Hazardous combustion products:  
In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO<sub>2</sub>), Nitrous gases (NO<sub>x</sub>)
- 5.4 Special protective equipment for fire-fighters:  
Wear a self-contained breathing apparatus and chemical protective clothing.
- 5.5 Additional information:  
Do not inhale explosion and combustion gases. Co-ordinate fire-fighting measures to the fire surroundings.  
Do not allow run-off from fire-fighting to enter drains or water courses. Move undamaged containers from immediate hazard area if it can be done safely.

## 6. Accidental release measures

- 6.1 Personal precautions:  
Avoid generation of dust. Remove all sources of ignition.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
Remove persons to safety.  
See protective measures under point 7 and 8.
- 6.2 Environmental precautions:  
Do not allow to enter into soil/subsoil.  
Do not allow to enter into surface water or drains.
- 6.3 Methods and material for containment and cleaning up:  
Suitable material for taking up: Water  
Take up mechanically, placing in appropriate containers for disposal. Avoid generation of dust.

## 7. Handling and Storage

- 7.1 Precautions for safe handling:  
7.1.1 Advices on safe handling:  
It is recommended to design all work processes always so that the following is excluded:  
Inhalation of dust/particles, skin contact, eye contact, depositing of dust.  
Working places should be designed allow cleaning at any time.  
Wear personal protection equipment (refer to section 8).
- 7.1.2 Measures to prevent fire:  
The product is: explosive.  
Keep away from sources of ignition - No smoking.  
Handle with care - avoid bumps, friction and impact.  
Wear anti-static footwear and clothing.  
Take precautionary measures against static discharges.
- 7.1.3 Measures to prevent aerosol and dust generation:  
Provide adequate ventilation as well as local exhaust at critical locations.
- 7.1.4 Advices on general occupational hygiene  
When using do not eat, drink, smoke, sniff.  
Wash hands before breaks and after work.  
Take off immediately all contaminated clothing.
- 7.2 Conditions for safe storage, including any incompatibilities:  
7.2.1 Technical measures and storage conditions:  
Storage temperature: 0 °C (32 °F) to + 30 °C (86 °F)  
Recommended storage temperature: + 20 °C (68 °F)  
Relative air humidity: max. 70 %

Title							
PRIMER CAPS MEDIUM 6.17 MM SINOXID							
<b>RUAG</b>	Protection notices DIN ISO 16016		Doc-Typ	Document	Part	Version	Page
			ZSD	362361	EN0	00	3/7

Dok-Status: FR

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

7.2.2 Requirements for storage rooms and vessels:  
Keep/store only in original container.  
Store in a place accessible by authorized persons only.

7.2.3 Hints on joint storage:  
Do not store together with inflammable or other substances that mean an increase of risk.  
Observe in addition any national regulations.

7.2.4 Storage class: Explosive substances  
Storage class: 1.4  
Compatibility group: S

## 8. Exposure controls / Personal protection

8.1 Exposure limit values:

8.1.1 Occupational exposure limits (OEL):

CAS-No. EC-No.	Limit value type (country of origin)	Substance name	OEL		Peak limitation	Remarks / Source
			ml/m <sup>3</sup>	mg/m <sup>3</sup>		
630-08-0 211-128-3	AGW (DE)	Carbon monoxide	30	35	1(II)	TRGS 900
124-38-9 204-696-9	AGW (DE)	Carbon dioxide	5000	9100	2(II)	TRGS 900
	AGW (DE)	A: Alveolar fraction E: Respirable fraction		1.25 10	2(II)	TRGS 900

8.1.2 Biological occupational exposure limit values:

CAS-No. EC-No.	Limit value type (country of origin)	Substance name	Parameter	Limit value	Test material	Remarks / Source
630-08-0 211-128-3	BGW (DE)	Carbon monoxide	CO-Hb	5 %	Whole blood (B)	TRGS 903

8.2 Exposure controls:

8.2.1 Appropriate engineering controls:

See section 7. Any further measures are not necessary.

8.2.2 Personal protection equipment:

Respiratory protection: No personal respiratory protective equipment normally required.

Dust formation: Filtering Half-face mask (DIN EN 149) FFP2

Hand protection: Hand protection is not required

Eye protection: Eye glasses with side protection or visor made of safety glass.

Protective clothing: Wear anti-static footwear and clothing.

Protection of the ears: Necessary.

8.3 Additional information:

Preventive industrial medical examinations are to be offered.

## 9. Physical and chemical Properties

No data available, article.

## 10. Stability and Reactivity

10.1 Conditions to avoid:

In case of warming:

Danger of explosion

In case of impact or pressure influence:

Danger of explosion

Reaction takes place at temperatures above:

ca. 150 °C (302 °F)

10.2 Materials to avoid:

Reaction: Acid, Alkali (Lye)

Title							
PRIMER CAPS MEDIUM 6.17 MM SINOXID							
<b>RUAG</b>	Protection notices DIN ISO 16016		Doc-Typ	Document	Part	Version	Page
			ZSD	362361	EN0	00	4/7

Dok-Status: FR

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

- 10.3 Hazardous decomposition products:  
Thermal decomposition can lead to the escape of irritating gases and vapours.  
Exothermal decomposition with formation of: carbon monoxide, carbon dioxide, nitrous gases (NOx),  
metal oxides

## 11. Toxicological information

- 11.1 General remarks:  
No harmful effects are to be expected if used properly.  
The contained ingredients can be harmful for humans, but they are hermetically enclosed in the article and cannot be released. The dismantling of the article is prohibited.

## 12. Ecological information

- 12.1 General remarks:  
No harmful effects are to be expected if used properly.  
The contained ingredients can be harmful for the environment, but they are hermetically enclosed in the article and cannot be released. The dismantling of the article is prohibited.

## 13. Disposal considerations

- 13.1 Product/Packaging disposal:  
Dispose of waste according to applicable legislation. Non-contaminated packages may be recycled.
- 13.2 List of proposed waste codes/waste designations in accordance with AVV:  
Waste codes product: 16 04 03\*  
Waste name: Other waste explosive  
Remark: Hazardous waste
- 13.3 Additional information:  
Completely ignited articles may be recycled.

## 14. Transport information

- 14.1 Land / sea / air transport:

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
Official transport designation	Anzündhütchen Primers, cap type Amorces à percussion		
Class	1.4S		
UN-No.	0044		
Packing group	-		
Special provisions	-		A802
Limited quantity	0		forbidden
Tunnel restriction code	E	not applicable	not applicable
EmS-No.	not applicable	F-B, S-X	not applicable

Title <b>PRIMER CAPS MEDIUM 6.17 MM SINOXID</b>							
<b>RUAG</b>	Protection notices DIN ISO 16016		Doc-Typ <b>ZSD</b>	Document <b>362361</b>	Part <b>EN0</b>	Version <b>00</b>	Page <b>5/7</b>

Dok-Status: FR

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

- 14.2 Packaging:  
Permitted packing according to packing instructions:  
According to ADR/RID/IMDG: P133  
According to ICAO-TI/IATA-DGR: 133  
Inner: e.g. receptacles of plastic, fibreboard or trays of plastic, fibreboard  
Intermediate: only required, when the inner packagings are trays,  
e.g. receptacle of fibreboard  
Outer: type approved and authorized box of packing group II:  
e.g. of fibreboard (4G) or of natural wood, ordinary (4C1)

- 14.3 Information of mass:  
Net explosive quantity (NEQ) per article: ca. 0.06 g  
Total mass per article: ca. 1 g

- 14.4 Additional information:  
Exemptions (1.1.3.6 ADR): unlimited.  
Approvals US Department of Transportation (DOT):  
7213: EX2002060244

## 15. Regulatory information

- 15.1 Safety, health and environmental regulations/specific legislation:

- 15.1.1 EU-Legislation:  
Directive 2014/28/EU relating to the making available on the market and supervision of explosives for civil uses.  
Regulation (EC) No. 1272/2008 on classification, labelling and packaging of substances and mixtures.

- 15.1.2 Authorisations:  
The following EC-Type Examination Certificates of the Federal Institute for Materials Research and Testing (BAM) are available:  
PRIMER CAPS MEDIUM 6.17 MM SINOXID: 0589.EXP.4272/06

- 15.1.3 National regulations:  
Observe in addition any national regulations!

### Germany:

Water hazard class (WGK): Article, not applicable

To follow: Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Chemikaliengesetz (ChemG)  
Sprengstoffgesetz (SprengG)  
Waffengesetz (WaffG)  
Beschussgesetz (BeschussG)  
Kriegswaffenkontrollgesetz (KWKG)  
Gefahrstoffverordnung (GefStoffV)  
Technische Regeln für Gefahrstoffe: TRGS 510, 900, 903, 905  
Berufsgenossenschaftliche Vorschriften: DGUV Regel 113-017

Title								
PRIMER CAPS MEDIUM 6.17 MM SINOXID								
<b>RUAG</b>	Protection notices DIN ISO 16016		Doc-Typ	Document	Part	Version	Page	

Dok-Status: FR

# VOLUNTARY SAFETY INFORMATION

FOLLOWING THE SAFETY DATA SHEET FORMAT ACCORDING TO REGULATION (EC) NO. 1907/2006 (REACH)

## 16. Other information

16.1 Indication of changes: First edition.

16.2 Relevant H- and EUH-phrases (Number and full text):

H-phrases:

- 200 Unstable explosives.
- 272 May intensify fire; oxidiser.
- 302+332 Harmful if swallowed or if inhaled.
- 351 Suspected of causing cancer.
- 360Df May damage the unborn child. Suspected of damaging fertility.
- 373 May cause damage to organs through prolonged or repeated exposure.
- 400 Very toxic to aquatic life.
- 410 Very toxic to aquatic life with long lasting effects.

16.3 Additional information:

The above information describes exclusively the safety requirements of the article and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the article for storage, processing, transport and disposal. The information cannot be transferred to other articles.

Title								
PRIMER CAPS MEDIUM 6.17 MM SINOXID								
<b>RUAG</b>	Protection notices DIN ISO 16016		Doc-Typ	Document	Part	Version	Page	7/7
			ZSD	362361	EN0	00		

Dok-Status: FR